Listing of Claims:

This listing of claims reflects all claim amendments and replaces all prior versions, and listings, of claims in the application. Material to be inserted is in **bold and underline**, and material to be deleted is in ~~strikeout~~ or (if the deletion is of five or fewer consecutive characters or would be difficult to see) in double brackets [[ ]].

Please amend claims 11-23 as indicated below.

1-10. (Canceled)

11. (Currently Amended) A mobile joint (1) for a seating construction for mounting between a seat device (100) of a seating construction and a support (200) for said seat device (100), comprising at least two joint elements (10, 30) wherein each joint element ~~may be pivoted~~ **is pivotable** to a limited degree in relation to each joint element that it is connected to, permitting the mobile joint (1) to pivot between two extreme positions in order to allow a tilting movement of the seat device (100), effected by the ~~users~~ **user's** weight displacement, ~~characterized in that it~~ **wherein the mobile joint** contains a first joint element (10) ~~mounted in~~ **mountable at** a first end to the support (100) and ~~in~~ **at** a second end only mounted **pivotally** ~~pivotal~~ to a first end of a middle joint element (20) ~~in~~ **at** a first rotational axis (40), and further containing a second joint element (30) ~~mounted in~~ **mountable at** a first end to the seat device (200) and ~~in~~ **at** the second end only mounted **pivotally** ~~pivotal~~ to a second end of the middle joint element (20) in a second rotational axis (50), wherein the said rotational axes (40, 50)

are horizontally displaced in relation to each other, and whereby the joint (1) ~~may assume~~ **assumes** a stable tilting position between the two extreme positions **when the user's center of gravity is above a point between the first and second rotational axes**.

12. (Currently Amended) The mobile joint (1) of claim 11, ~~characterized in that~~ **wherein** the middle joint element (20) consists of a number of joint sub-elements, wherein the mobile joint (1) **is configured to assume** ~~may take~~ a number of additional stable tilting positions between the two extreme positions.

13. (Currently Amended) The mobile joint (1) of claim 11, ~~characterized in that~~ **wherein** the horizontal distance between the rotational axes (40, 50) is about 5-15 cm.

14. (Currently Amended) The mobile joint (1) of claim 13, ~~characterized in that~~ **wherein** the horizontal distance between the rotational axes (40, 50) is about 6-10 cm.

15. (Currently Amended) The mobile joint (1) of claim 11, ~~characterized in that~~ **wherein** the tilted positions of each joint element are restricted by pairs of reciprocally cooperating fitting surfaces (12, 21; 14, 23; 33, 22; 35, 26), where each pair of reciprocally cooperating fitting surfaces is configured to abut when a joint element is pivoted to a desired point, thereby hindering further movement of the joint element.

16. (Currently Amended) The mobile joint (1) of claim 15, ~~characterized in that~~ **wherein** one or both members of ~~a~~ **at least one** pair of cooperating fitting surfaces (12, 21; 14, 23; 33, 22; 35, 26) ~~are~~ **is** equipped with ~~rotational stoppers~~ **a stopper** (13, 24, 34, 36)**, wherein the stopper is** configured to dampen the impact ~~of~~ **between** the pair of cooperating fitting surfaces **when the corresponding joint element is pivoted to the desired point**.

17. (Currently Amended) The mobile joint (1) of claim 11, ~~characterized in that~~ **wherein** at least two of the joint elements (10, 20, 30) are spring-loaded in relation to each other.

18. (Currently Amended) The mobile joint (1) of claim 17, ~~characterized in that~~ **wherein** the spring-load is created by a torsion spring, a spring coil, a plate spring, or an elastic material.

19. (Currently Amended) The mobile joint (1) of claim 18, ~~characterized in that~~ **wherein** the spring-load is created by a torsion spring.

20. (Currently Amended) The mobile joint (1) of claim 17, ~~characterized in that~~ **wherein** the spring load is adjustable.

21. (Currently Amended) The mobile joint (1) of claim 17, ~~characterized~~

~~in that~~ **wherein** the first and second joint elements (10, 30) have different spring-loads in relation to the middle joint element.

22. (Currently Amended) The mobile joint (1) of claim 11, ~~characterized in that~~ **wherein** at least two joint elements (10, 20, 30) ~~may be locked~~ **are lockable** in relation to each other.

23. (Currently Amended) A chair comprising a mobile joint (1) according to one of claims 11-21, the joint being mounted between a seat device (100) and a support (200) for said seat device (100).